



Ref. No. Drawing no 60.511b

Specification Terminal Trailer (Bumb Cart) 45'/65t .

Capacity: Pay Load 65 tons.
Tara weight 8,5 tons

Overall dimensions:

Length: abt 14.260 mm
Width: abt. 2.800 mm
Height: In front: abt.1550 mm
Over wheel set: abt. 1550 mm
Coupling height: 1240 mm

Container bed dimensions:

Length: 13866 mm (45' + 150 mm)
Width: 2500 mm.

Container loading: 1x 20' or 2x20' ISO container of 30 ton each or
1x 40' ISO container of 33 ton or
1x45' ISO container of 33 ton

Max. 5th wheel load: 32 t.

Max. Axle load: 22 t.

Kingpin: 2"

Track: abt 2100 mm.

Wheels: 11R22.5 or 315/80R22.5

Axle: 2 Rockerarm with heavy duty axles.

Base features: Opened corners,
Material for main beams are IPE500 in St. 52-3 or better
Longitudinal beams to be placed as close to container support beam as possible
Automatic stops of gravity type for 20', 40 containers.
Round edge rigid guides for smooth and damagefree containers loading.
Front landing support with foldable lower part.



- Brake System:** On two axles. The trailers brake system is connected to the Tugmaster pneumatic brake system.
- Light System:** Standard light system is installed on the trailer.
The light system is will be connected to the Tuckmaster light system.
- Finish:** Trailer complete shot blasted to SSI 55900 AS 2,5 after welding
Painting with Epoxy Primer and Polyethylen Topcoat, 1x primer and 1x topcoat Ral code to be agreed.
Total thickness 120 micron.
- Marking** Costume logo on 2 side of trailer provided SWL 65 tons
Tare weight on 2 sides.
2 nos red triangle reflectors at the rear end of trailer